Ficha Técnica
Technical sheet

BRUMA

Produto | Product

Sistema termostático embutido de duche com chuveiro Line Cascade (Chuva/Cascata) e chuveiro mão | *Thermostatic concealed shower set with Line Cascade shower (Rain/Cascade) and handshower set*


185 595 2XX


IMAGEM* | *IMAGE**





DESENHO DIMENSIONAL | *DIMENSIONAL DRAWING*





ESPECIFICAÇÕES | *SPECIFICATIONS*

- Sistema termostático embutido de duche com chuveiro Line Cascade (Chuva/Cascata) e chuveiro mão;
- Cartucho termostático;
- Tecnologia para menor consumo de água BRUMA AirEcoDrop®;
- Sistema anticalcário BRUMA ConfortClean®;
- Chuveiro de mão com redutor de caudal 6 l/min;
- Limitador de temperatura a 38°C;
- Com elemento encastrável INT 630 2NO.

- Thermostatic concealed shower set with Line Cascade shower (Rain/Cascade) and handshower set;
- Thermostatic compact cartridge;
- Water-saving technology BRUMA AirEcoDrop®;
- Anti-limescale system BRUMA ConfortClean®;
- Hand shower with flow reducer 6 l/min;
- Safety stop limits the temperature range to 38 °C;
- With concealed body INT 630 2NO.




DIAGRAMA CAUDAL | *FLOW DIAGRAM*

Caudais a 3 bar:
- Chuveiro de mão: 6,0 l/min.
- Chuveiro Cascade (chuva): 12,5 l/min.
- Chuveiro Cascade (cascata): 9,4 l/min.

Flow rate at 3 bar
- Handshower: 6,0 l/min.
- Chuveiro Cascade (chuva): 12,5 l/min
- Chuveiro Cascade (cascade): 9,4 l/min.

EFICIÊNCIA HÍDRICA | *WATER LABEL* **A +**

INSTRUÇÕES DE MANUTENÇÃO | *MAINTENANCE INSTRUCTIONS*

* Imagem não contratual | **Non-contractual image*

Ficha Técnica
Technical sheet


BRUMA

Produto | Product


Elemento encastrável | *Concealed body*

INT 630 2NO

IMAGEM* | *IMAGE**



DESENHO DIMENSIONAL | *DIMENSIONAL DRAWING*



ESPECIFICAÇÕES | *SPECIFICATIONS*

- Elemento encastrável;
- Cartucho termostático com elemento sensível Vernet;
- Cartucho inversor de discos cerâmicos;
- Inclui parafusos e buchas para fixação.

- Concealed body;
- Thermostatic cartridge with Vernet sensitive element;
- diverter cartridge with ceramic discs;
- Screws and plugs included.





DIAGRAMA CAUDAL | *FLOW DIAGRAM*

Caudais a 3 bar:
- Saída 1 (sem restrição): 26,30 l/min
- Saída 2 (sem restrição): 24,70 l/min
- Saída 3 (sem restrição): 24,70 l/min

Flow rate at 3 bar:
- Outlet 1 (without restrictor): 26,30 l/min
- Outlet 2 (without restrictor): 24,70 l/min
- Outlet 3 (without restrictor): 24,70 l/min



* Imagem não contratual | **Non-contractual image*