

F111

+135°
-30°

PA6
+G.F.

RoHS
COMPLIANT

06

6 6 / 6 6

6:
6 6666
666 6666 66

6 6:
6666 (666 66 6666).


6:
6 (RAL 9011).

66:
66 66 66 6666 6666 (666 66 6g).

66 66 66:
66 66 66 6666, 66 66 66 66 6666 6666 66 66.
66 66 66 66 6666 66, 6666 6666 6666 6666 66 6666.
66 66 66 66 66 66 66 66 6666 6666 66 666666 (66: 66 6666 666666).



© Copyright
Boteco srl Unipersonale



© Copyright
Boteco srl Unipersonale

66	Art.	D	d	H	m	c	d16g	Q	LM	66(g)
F111022.0001	F111022.TM04X1601	22	12	17.5	11	6.5	M4	16	50	6
F111022.0002	F111022.TM04X3001	22	12	17.5	11	6.5	M4	30	50	7
F111022.0003	F111022.TM05X1601	22	12	17.5	11	6.5	M5	16	50	7

??	Art.	D	d	H	m	c	d16g	Q	LM	??(g)
F111022.0005	F111022.TM05X3001	22	12	17.5	11	6.5	M5	30	50	8
F111027.0001	F111027.TM05X2001	27	14	22	13	9	M5	20	60	10
F111027.0002	F111027.TM05X4001	27	14	22	13	9	M5	40	60	11
F111027.0003	F111027.TM06X2001	27	14	22	13	9	M6	20	60	12
F111027.0005	F111027.TM06X4001	27	14	22	13	9	M6	40	60	13
F111033.0001	F111033.TM08X2001	33	19	26	15	11	M8	20	70	18
F111033.0002	F111033.TM08X4001	33	19	26	15	11	M8	40	70	22
F111033.0003	F111033.TM10X2001	33	19	26	15	11	M10	20	70	24
F111033.0005	F111033.TM10X5001	33	19	26	15	11	M10	50	70	27

LM = ?? ?? ?? ??