


F175BF



06

6-lobed handwheels

6-lobed handwheels

200°C 130°C ISO 22196:2011 ATCC 25922 • ATCC 10231 • ATCC 13388 • ATCC 15442 • ATCC 4352 • ATCC 6538. 99.5% 99.9%

BF

200°C 130°C ISO 22196:2011 ATCC 25922 • ATCC 10231 • ATCC 13388 • ATCC 15442 • ATCC 4352 • ATCC 6538. 99.5% 99.9%

200°C 130°C ISO 22196:2011 ATCC 25922 • ATCC 10231 • ATCC 13388 • ATCC 15442 • ATCC 4352 • ATCC 6538. 99.5% 99.9%

BF

200°C 130°C ISO 22196:2011 ATCC 25922 • ATCC 10231 • ATCC 13388 • ATCC 15442 • ATCC 4352 • ATCC 6538. 99.5% 99.9%

BF

(RAL 9011).

BF



(AISI 303)(6H).

BF

BF



© Copyright Boteco srl Unipersonale



© Copyright Boteco srl Unipersonale

??	Art.	D	H	d	c	m	d3	h3	d16H	Q	??(g)
F17530.0005	F17530.TM0501BF	30	22	15	11	11	9	1.5	M5	14	11.5
F17530.0011	F17530.TM0601BF	30	22	15	11	11	9	1.5	M6	10	12
F17540.0005	F17540.TM0601BF	40	24.5	17	12	12.5	12	1	M6	16	22
F17540.0011	F17540.TM0801BF	40	24.5	17	12	12.5	12	1	M8	14	21.5
F17550.0007	F17550.TM0801BF	50	29	20	14	15	14.5	1.5	M8	14	36
F17550.0015	F17550.TM1001BF	50	29	20	14	15	14.5	1.5	M10	14	37
F17560.0007	F17560.TM1001BF	60	34	24	16	18	18	1.5	M10	21	59
F17560.0015	F17560.TM1201BF	60	34	24	16	18	18	1.5	M12	18	62