

G632

UPDATE

+135°
-30°

PA6
+G.F.

RoHS
COMPLIANT

07

4 44 44 / 444(PUSH TO USE) 444, 444

4-lobe handwheels

44:

(3-4) 44 44 44 44 444444(technopolymer).

444 4444 44.

44 44:

4444 (444 44 4444).

44:

(3-4)44. (RAL 9011).

44 44 44:

(1) 44 444444(polyamide) (RAL 3000 cod. 16)

- 44444 4444 44 44:
- 4444: (RAL 2004 cod. 02).
- 44 (RAL 5015 cod. 07).
- 44 (RAL 1021 cod. 10).
- 44 (RAL 3000 cod. 16).
- 44 (RAL 6024 cod. 17).
- 44 (RAL 7035 cod. 13).
- 44 (RAL 9001 cod. 01).

444:

44 44 44 4444 444(444 44 6g).

444:

44444 44 444 (AISI 302)

44 44 44:

44 44 44 444, 44 44 44 444 444 44 44.

44 4 44 44 444 44, 44444 4444 444 44 4 4444.

44 4 4 44 44 44 4 444 444444 44 44444.

44	art.	D	H	d2	d	m	c	LM	d16g	Q	44(g)
G63250.0002	G63250.TM06X300116	49	42.5	22	15	13	22	90	M6	30	-
G63250.0005	G63250.TM08X400116	49	42.5	22	15	13	22	90	M8	40	-
G63250.0007	G63250.TM10X500116	49	42.5	22	15	13	22	90	M10	50	-

LM = 44 4444 44

2504 44 444, 44 44 44 44.

