

O400

+135°
-30°

PA6
+G.F.

RoHS
COMPLIANT

15

?? ???? ?? ??

Plastic hinges with through holes

??:
?? ??????
???? ????? ??

?? ??:
???? (???? ?? ?????).

??:
?? (RAL 9011).

???:
?? ?? ?? ?

?:
?? TS:
???? ????? ?? ?? ??, DIN 7991 / UNI 5933 ????? ?
?? TC:
???? ????? ?? ?? ??, DIN 912 / UNI 5931 ????? ?? ????? ?


?? ?? ??:
?? ?



© Copyright
Boteco s.p.a. - Unipersonale



© Copyright
Boteco s.p.a. - Unipersonale



?? O400-TS: ??? ???? ??

??	art.	I	C	A	B	h	H	D	d2	d3	d1	??(g)	F1 (N)	F2 (N)
O40020.0003	O40020.TG04.501TS	20	20	32	32	7	10,5	8,5	3	7	4,5	9	1440	490
O40030.0003	O40030.TG05.501TS	30	30	48	48	10,5	15,5	12,5	5	10	5,5	27	1960	1470
O40030.0007	O40030.TG06.501TS	30	30	48	48	10,5	15,5	12,5	5	10	6,5	27	1960	1470
O40040.0004	O40040.TG06.501TS	40	40	64	64	13	19	12,5	5	12	6,5	53	2850	1520
O40060.0003	O40060.TG08.501TS	60	63	96	96	16	24	16,5	8	16	8,5	152	4300	1810
O40060.0007	O40060.TG10.501TS	60	63	96	96	16	24	20,5	8	16	10,5	152	4300	1810

?? O400-TS: ??? ???? ??

??	art.	I	C	A	B	h	H	D	d2	d3	d1	??(g)	F1 (N)	F2 (N)
O40020.0001	O40020.TG04.501TC	20	20	32	32	7	10,5	7,5	3	7	4,5	9	1440	490
O40030.0001	O40030.TG05.501TC	30	30	48	48	10,5	15,5	10,5	5	10	5,5	27	1960	1470
O40030.0005	O40030.TG06.501TC	30	30	48	48	10,5	15,5	10,5	5	10	6,5	27	1960	1470
O40040.0002	O40040.TG06.501TC	40	40	64	64	13	19	10,5	5	12	6,5	53	2850	1520
O40060.0001	O40060.TG08.501TC	60	63	96	96	16	24	13,5	8	16	8,5	152	4300	1810
O40060.0005	O40060.TG10.501TC	60	63	96	96	16	24	16,5	8	16	10,5	152	4300	1810